



COMMERCIAL DRAINAGE PRODUCTS

Drainage Board Type II™ is a high-flow dimpled core bonded to a single layer of non-woven filter fabric. Type II is designed as a commercial composite drainage and is intended for both vertical and horizontal application.

Drainage Board Type III™ consists of a heavy-duty, high-density polyethylene geonet drainage core with a coated filter fabric on both sides. Type III is ideal for flat decking, retaining walls and bridge abutments.

DRAIN-A-WAY™ 12" is a drainage and collection system consisting of a thick dimpled drainage core completely wrapped with a filter fabric. It is used for the collection and disposal of water and replaces the pipe and gravel drains on foundations and retaining walls.

Composite Drainage Properties¹

PRODUCT (ROLLS)	THICKNESS	COMPRESSION psf	FLOW RATE gpm/ft. width
TYPE II SIZE: 4' X 50'	.40?	15,000	1:15
TYPE III SIZE: 4' X 50'	.25?	30,000	1:7
DRAIN-A-WAY 12? SIZE: 12' X 165'	1?	7,500	1:30

Geo-Mat™ Plus is made of a high-density polyethylene (HDPE) with an attached polypropylene geotextile mat. Designed to provide excellent protection and drainage.

Geo-Mat Plus Properties¹

PRODUCT (ROLLS)	THICKNESS	COMPRESSION lb/in	FLOW RATE gpm/ft. width
GEO-MAT PLUS SIZE: 8' X 50'	.2968?	>29	30.1

DRAIN & DRY BOARD is a semi-rigid thermal insulation board made from inorganic glass fibers, preformed into boards, and bonded by a thermo setting resin. It is intended for use in conjunction with Mar-flex waterproofing membranes. It is available in thermal values of R-3.1 to R-10.0, to meet the needs of builders, energy conscious homebuyers and/or local building codes.

Drain & Dry Board Properties¹

PRODUCT (BOARD)	R-VALUE	COMPRESSION lb/in	FLOW RATE GH/L
3/4? SIZE: 3' X 4'	3.1	46.8	126.8
1-3/16" SIZE: 3' X 4'	5.0	22.72	249.1
2-3/8? SIZE: 3' X 4'	10.0	30.72	291.4

QuickSilver Foundation Drainage Board is constructed of expanded polystyrene with a 1-mil metallic polypropylene laminate on one side and a 1-mil clear laminate on the other side. Each board features 22 slots, 0.03125" from top to bottom with a depth of 1/4".

QuickSilver Properties

PRODUCT (BOARD)	R-VALUE	COMPRESSION lb/in ²	FLOW RATE GH/L
3/4" SIZE: 3' X 4'	2.8	10	11.7
1-3/8" SIZE: 3' X 4'	5.1	10	11.7
2-3/4" SIZE: 3' X 4'	10.2	10	11.7

HEALTH AND SAFETY INFORMATION IS GIVEN IN THE MATERIAL SAFETY DATA SHEET AVAILABLE FOR THIS PRODUCT. THE MATERIAL SAFETY DATA SHEET SHOULD BE READ AND UNDERSTOOD BEFORE USING THIS PRODUCT.

PRODUCT DATA

Division 7

Mar-flex Waterproofing and Basement Products
6866 Chrisman Lane, Middletown, OH 45042
(800) 498-1411 | (513) 422-7285 | Fax – (513) 422-7282
E-mail: keepdry@mar-flex.com
Web-site: www.mar-flex.com
Rev. 10/07

¹ ASTM Methods Available Upon Request